1/2

PRODUCT FICHE

Appliance status: O Valid from: 19.12.2012 Last modification: 2.7.2020 1:31:52

# gorenje



#### Kitchen hood 185611 DF6115W

#### USP:

Number of speed positions	3
Number of lights	2
Lamp type	Regular
Illumination setting	On/off light switch
Number of filters	2
Washable grease filter	✓
Filter material	Aluminium
Washable grease filter	✓
Coal filter code (optional as separate purchase	646780
Grease filter code	194502
Air flow by extraction version, step 1	141 m³/h
Air flow by extraction version, step 2	174 m³/h
Maximum extraction rate by extraction operation	225 m³/h
Noise level (min.)	49 dB(A)re 1 pW
Max. noise level	58 dB(A)re 1 pW
Power input/speed III	180 W

#### **Basic information:**

	12: 1
Product group	Kitchen hood
Decor panel options	N/A
Construction type	Built-in
Brand	Gorenje
Product name / Family	Kitchen hood
Commercial code	DF6115W
Internal article number	185611
EAN code	3838942407956
Color body	White
Material body	Painted steel
Typology	Ttelescopic
Installation type	Instead of cabinet
Motor location	Motor integrated in the hood
Operating mode	Convertible
Connection Rating	176 W
Current	10 A
Voltage	220-240 V
Frequenc	50 Hz
Approval certificates	CE
Length of electrical supply cord	150 cm
Plug type	Euro
Height of product, without chimney	173 mm
Net weight	7,4 Kg
Gross weight	8,4 Kg
Width of the product	598 mm
Height of the product	173 mm
Depth of the product	295 mm
Width of the packed product	660 mm
Height of the packed product	390 mm
Depth of the packed product	225 mm
Air exhaust	Yes

## Features:

Remote control	N/A
Short description of the product	E123 I 1K282ASB-DF6115W
Type of control	Mechanical
Type of manual control devices	Switches
Number of motors	1
Total power of the motors	120 W
Number of speed settings	3
Boost position	No

185611 2/2

Maximum output air extraction 225 m³/h Maximum output recirculating air 180 m³/h ON/OFF Illumination setting Number of lights 2 Type of lamps used Regular lamp Total power of the lamps 56 W 58 dB(A) re 1 pW Max. noise level Diameter of air outlet 120 No-return airflow flap Yes Grease filter material Washable aluminium Odour filter No

### Energy label information / Performance:

Air flow at intenstive or boost setting	N/A
Maximum Air flow	225 m³/h
Minimum air flow	141 m³/h
Total annual energy consumption	N/A
Energy efficiency class	N/A
Fluid Dynamic Efficiency class	N/A
Grease filtering efficiency class	N/A
Lighting efficiency	N/A
Noise level with boost position	N/A
Sound power at max. speed	58 dB
Sound power at min. speed	49 dB
Maximum extraction rate by extraction operation	225 m³/h
Energy efficiency index (2010/30/EC)	0,0 %
Fluid Dynamic Efficiency (2010/30/EC)	0,0
Grease filtering efficiency (2010/30/EC)	N/A
Lighting efficiency (2010/30/EC)	0,0
Noice level with boost position	N/A
Power consumption in standby mode (2010/30/EC)	N/A
Power consumption in off-mode - NEW (2010/30/EC)	N/A