

## Spray cleaning Partial spray



	Description
Definition/Objective	To <b>spot clean highly stubborn soiling</b> on floor coverings <b>using the single-brush machine.</b> Use the spray application product to <b>restore worn areas in the protective film.</b> Suitable for smooth or slightly textured floor coverings.
Preparatory work	Select suitable products to match the surface to be cleaned (type / square metres) and the type of soiling.
	Check, equip and ready the machine and all accessories in compliance with the instructions for use.
	Fill the spray cleaning product into the spray unit in accordance with the dosing instructions.  Close the spray unit and build up pressure (pumping). Position the spray nozzle correctly.
	Put up the warning sign.
	Remove any loose dirt (dust-binding mopping).
Main task	Attach the scrubbing pad with the pad drive disc to the single-brush machine.
	Set the correct height for the upright handle.
	Switch on the machine. The connection must audibly click into place.
	Spray a <b>small amount of the spray product</b> onto the <b>soiled spot</b> and scrub it dry immediately using the single-brush machine LS and the scrubbing pad. Continue working on the next section.
	Reverse or replace dirty pads as needed.
	Polish the cleaned area.
	Perform a visual check.
Final steps	Clean the spray unit in accordance with the operating instructions.
	Check the power cable for visible damage, clean the cable and roll it up loosely towards the plug.
	Remove the warning sign.
	Rinse the used pads or wash them in the washing machine.
	Dispose of any waste.
	Clean the cleaning materials and replace as needed.
Comments	<ul> <li>Wear the personal protective equipment (PPE) required by company regulations, safety data sheets and / or instructions for use.</li> <li>Always check in advance which product meets your requirements (see Wetrok Cleaning &amp; Care Instructions).</li> <li>Wetrok AG accepts no liability for damage caused by improper use or incorrect product selection.</li> </ul>