



SP 15

Paving width**	max. 1,800 mm***
Paving height**	max. 1,300 mm
Engine power	92 kW / 123 HP / 125 PS
Operating weight, CE*	10,000 - 13,500 kg
Exhaust emission standard	EU Stage 3a / US EPA Tier 3



SP 15i

Paving width**	max. 1,800 mm***
Paving height**	max. 1,300 mm
Engine power	95 kW / 127 HP / 129 PS
Operating weight, CE*	10,000 - 13,500 kg
Exhaust emission standard	EU Stage 5 / US EPA Tier 4f



SP 20

Paving width**	max. 2,500 mm
Paving height**	max. 2,000 mm
Engine power	118 kW / 158 HP / 160 PS
Operating weight, CE*	11,000 - 18,900 kg
Exhaust emission standard	EU Stage 3a / US EPA Tier 3



SP 20i

Paving width**	max. 2,500 mm
Paving height**	max. 2,000 mm
Engine power	115 kW / 154 HP / 156 PS
Operating weight, CE*	11,000 - 18,900 kg
Exhaust emission standard	EU Stage 5 / US EPA Tier 4f

* Weight of machine, half weight of all consumables, machine operator (75 kg), on-board tool kit, no optional equipment; weights depend on the actual equipment installed and the working width

** Please consult factory for different offset geometries or special applications

*** Paving width up to 2,200 mm available on request



SP 25

Paving width**	max. 2,500 mm
Paving height**	max. 2,000 mm
Engine power	118 kW / 158 HP / 160 PS
Operating weight, CE*	11,500 - 22,500 kg
Exhaust emission standard	EU Stage 3a / US EPA Tier 3



SP 25i

Paving width**	max. 2,500 mm
Paving height**	max. 2,000 mm
Engine power	115 kW / 154 HP / 156 PS
Operating weight, CE*	11,500 - 22,500 kg
Exhaust emission standard	EU Stage 5 / US EPA Tier 4f



SP 61

Paving width**	max. 4,000 mm
Paving height**	max. 3,000 mm
Engine power	155 kW / 208 HP / 211 PS
Operating weight, CE*	16,000 - 27,500 kg
Exhaust emission standard	EU Stage 3a / US EPA Tier 3



SP 61i

Paving width**	max. 4,000 mm
Paving height**	max. 3,000 mm
Engine power	180 kW / 241 HP / 245 PS
Operating weight, CE*	16,000 - 27,500 kg
Exhaust emission standard	EU Stage 5 / US EPA Tier 4f