



TP-Link Omada EAP623-Outdoor HD 1800 Mbit/s Wit Power over Ethernet (PoE)

Merk : TP-Link

Productfamilie: Omada

Artikelcode: EAP623-OUTDOOR HD

Productnaam : EAP623-Outdoor HD

TP-Link Omada EAP623-Outdoor HD. 2,4 GHz, 5 GHz, Maximale overdrachtsnelheid van gegevens: 1800 Mbit/s. Ondersteunde beveiligingsalgoritmen: SNMP, SNMPv2, SNMPv3, SSH. Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Kleur van het product: Wit



Kenmerken		Beheerfuncties	
2,4 GHz *	✓	Web-gebaseerd management	✓
5 GHz *	✓	Syslog	✓
6 GHz *	✗	Poorten & interfaces	
Maximale overdrachtsnelheid van gegevens *	1800 Mbit/s	Aantal Ethernet LAN (RJ-45)-poorten *	1
Maximale overdrachtsnelheid van gegevens (2.4 GHz)	574 Mbit/s	Energie	
Maximale overdrachtsnelheid van gegevens (5 GHz)	1201 Mbit/s	Power over Ethernet (PoE) *	✓
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Type Power over Ethernet (PoE) ondersteunt	Passive PoE
Frequentieband	2.4 - 5 GHz	Design	
Netwerkstandaard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Plaatsing *	Paal
Bekabelingstechnologie	10/100/1000Base-T(X)	Kleur van het product *	Wit
Aantal gebruikers	1020 gebruiker(s)	Reset button	✓
Automatische kanaalselectie	✓	LED-indicatoren	✓
Automatisch scannen kanalen	✓	Antenne	
MIMO	✓	Soort antenne *	Intern
MIMO-type	Multi User MIMO	Type antennerichting	Omni-directioneel
VLAN=ondersteuning	✓	Antennefuncties	Ingebouwde antenne
Rate limiting	✓	Antennas quantity	2
Bandbreedteaansturing	✓	Certificaten	
Airtime Fairness (ATF)	✓	Certificering	CE, FCC, RoHS
Quality of Service (QoS)	✓	Gewicht en omvang	
BeamForming	✓	Breedte	280,4 mm
Zendvermogen (CE)	< 20 dBm (2.4 GHz, EIRP), < 30 dBm (5 GHz, EIRP);	Diepte	106,5 mm
Zendvermogen (FCC)	< 25 dBm (2.4 GHz), < 25 dBm (5 GHz)	Hoogte	56,8 mm
Beveiliging		Inhoud van de verpakking	
Ondersteunde beveiligingsalgoritmen *	SNMP, SNMPv2, SNMPv3, SSH	Aantal per verpakking	1 stuk(s)
MAC adres filtering	✓	Montage gereedschap	✓
		Snelstartgids	✓

Beveiliging	Eisen aan de omgeving
Remote Authentication Dial-In User Service (RADIUS) ✓	Relatieve vochtigheid in bedrijf (V-V) 10 - 90 procent
Access Control List (ACL) ✓	Bedrijfstemperatuur (T-T) -30 - 70 °C
	Temperatuur bij opslag -40 - 70 °C
	Luchtvochtigheid bij opslag 5 - 90 procent



4895252506303

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-OCT-2024. Prints or copies of Information are only valid on the printed Publication date